



操作简单 实惠耐用
性价比高

SP32 技术参数(Technical Specification)

- 扣压最大胶管通径(Max. Hose ID): 2 寸
- 扣压力(Max Crimping Force): 450T
- 扣压范围(pipe diameter): 6-51MM
- 模具收扩(Die Opening & Closing): 25mm
- 最大张口(Opening Without Dies): 120mm
- 最小闭合(): 90mm
- 电机功率(Motor): 5HP-3.7KW
- 电源(Voltage): 220V/380V-50HZ
- 张合全程总耗时(Full Crimp Cycle): 10S
- 扣压控制精度(Accuracy): 0.01mm
- 扣压后产品不圆度(Un-even): ≤0.1mm
- 配送模具(Die-sets): 9 套 (2 分-2 寸)
- 外型尺寸(Dimensions): 630×440×590mm
- 包装尺寸: 700*500*830
- 净重: 180KG
- 毛重: 210KG

SP32 模具使用范围(Die-chart)

模具规格 Die No.	使用范围 Range	模具长度 Length	模具规格 Die No.	使用范围 Range	模具长度 Length
16	16-20	60	38	38-46	70
20	20-22	60	46	46-54	70
22	22-26	60	54	54-64	70
26	26-30	60	64	64-80	70
30	30-38	70			

SP32 压管机技术资料

TEL:18826870702